

Republic of the Philippines Department of Agriculture

SUGAR REGULATORY ADMINISTRATION

Sugar Center Bldg., North Avenue, Diliman, Quezon City, Philippines 1101 TIN 000-784-336

Website: http://www.sra.gov.ph Email Address: srahead@sra.gov.ph

Tel No. (632) 8929-3633, (632) 3455-2135, (632) 3455-3376

SUGAR REGULATORY ADMINISTRATION

North Avenue., Diliman, Quezon City

BIDS AND AWARDS COMMITTEE

SUPPLEMENTAL BID BULLETIN NO. 1

This **Supplemental Bid Bulletin No. 1** dated **15 April 2025** is issued to inform the prospective bidders of the following amendments, modifications and clarifications on the items in the Philippine Bidding Documents (PBDs) for the **PROCUREMENT OF SUPPLY AND DELIVERY OF ONE (1) UNIT BRAND NEW UV-VIS SPECTROPHOTOMETER** with Project ID No. **SRA2025-005** as previously posted in the Philippine Government Electronic Procurement System (PhilGEPS) and the Sugar Regulatory Administration (SRA) website. This Supplemental Bid Bulletin shall form an integral part of the Bidding Documents.

ORIGINAL BID DOCUMENT		CLARIFICATIONS/CORRECTIONS/CHANGES	
Section I. Invitation to Bid		Section I. Invitation to Bid	
9. Bid opening shall be on April 28, 2025 at the given address below SRA Social Hall, Sugar Regulatory Administration, North Avenue, Diliman, Quezon City through Physical or Face-to-Face. Bids will be opened in the presence of the bidders' representatives who choose to attend the activity.		9. Bid opening shall be on April 28, 2025 - 9:30 AM at the given address below SRA Social Hall, Sugar Regulatory Administration, North Avenue, Diliman, Quezon City through Physical or Faceto-Face. Bids will be opened in the presence of the bidders' representatives who choose to attend the activity.	
Section VII. Technical Specifications		Section VII. Technical Specifications	
Wavelength scanning speed	: 3,000 to 2 nm/min 29,000 nm/min when survey scanning	scanning speed Better nm/	00 to 2 nm/min ween 24,000- 29,000 /min when survey
Lamp interchange wavelength	: Automatic interchange linked to wavelength	interchange linke wavelength halo	omatic interchange ed to wavelength <u>for</u> ogen deuterium ps/ no interchange ded for xenon lamps

Supplemental Bid Bulletin No. 1 Supply and Delivery of One (1) Unit Brand New UV-VIS Spectrophotometer





BAGONG PILIPINAS

The interchange The interchange wavelength can be set wavelength can be set freely in the range of 295 to freely in the range of 295 to 34 nm (0.1 increments). 34 nm (0.1 increments). Photometric Less than ± 0.001 Abs at Photometric Less than ± 0.001 Abs repeatability 0.5 Abs repeatability at 0.5 Abs Less than ± 0.001 Abs at 1 Less than ± 0.001 Abs Abs at 1 Abs Less than ± 0.003 Abs at 2 Abs **Light Source** 20-W halogen and **Light Source** 20-W halogen and deuterium lamps Built-in deuterium lamps Built-in light source light source / xenon lamp Auto position adjustment Auto position adjustment

Prepared by:

Head, BAC Secretariat

Approved by:

Chairperson, Bids and Awards Committee